CERTIFICATE OF COMPLIANCE

Certificate Number 20170120-E303346

Report Reference E303346-20010126

Issue Date 2017-JANUARY-20

Issued to: ROTORK INSTRUMENTS ITALY SRL

VIA PORTICO 17

24050 ORIO AL SERIO BG ITALY

This is to certify that representative samples of

TELEMETERING EQUIPMENT FOR USE IN HAZARDOUS

LOCATIONS

See addendum for models.

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: See addendum for standards.

Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/



CERTIFICATE OF COMPLIANCE

Certificate Number 20170120-E303346

Report Reference E303346-20010126

Issue Date 2017-JANUARY-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Proximity bolt switch Series BL, followed by T1 or T2; followed by, 10, 13, 14, , C1, C3, C4, C6; followed by NL, GO, GC, RO or RC; followed by 018, 024, 036 or up to 3 characters, for use in Class I, Division 1, Groups A, B, C and D; Class II, Division 1, Groups E, F and G; Class III, Division 1 Hazardous Locations.

Proximity bolt switch Series BL, followed by T1, T2, A1 or A2; followed by 10, 13, 14, , C1, C3, C4, C6; followed by NL, GO, GC, RO or RC; followed by 018, 024, 036 or up to 3 characters for use in Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; Class III, Hazardous Locations.

Proximity bolt switch Series BM, followed by C1, C3, C4, C6; followed by 1; followed by any alphanumeric characters; followed by any alphanumeric characters; followed by 1, 2 or any alphanumeric characters; followed by 6, 1 or any alphanumeric characters; followed by any alphanumeric characters for use in Class I, Division 1, Groups A, B, C and D; Class II, Division 1, Groups E, F and G; Class III, Division 1 Hazardous Locations.

Proximity bolt switch Series BM, followed by C1, C3, C4, C6; followed by 1; followed by any alphanumeric characters; followed by any alphanumeric characters; followed by 1, 2 or any alphanumeric characters; followed by 6, 1 or any alphanumeric characters; followed by any alphanumeric characters for use in Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; Class III, Hazardous Locations.

Standards for Safety:

ANSI/ISA 12.12.01-2013, Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations

UL 1203, Explosion-Proof and Dust-Ignition-Proof Electrical Equipment for Use In Hazardous (Classified) Locations

UL 508, Industrial Control Equipment

C22.2 No. 213-M1987, Non-incendive Electrical Equipment for Use in Class I, Division 2 Hazardous Locations

C22.2 No. 30-M1986, Explosion-Proof Enclosures for Class I Hazardous Locations

C22.2 No. 25-1996, Enclosures for use in Class II Groups E, F and G Hazardous Location

C22.2 No.14-M1985 Industrial Control Equipment

Ba Wally

Bruce Mahrenholz Director North Am

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

